

DINAX® FILTER CLEANER F

filter elements and filter media descaling liquid

APPLICATION:

Cleaning sand filters and filter elements.

It can be used for paper or so-called accordion filter.

The liquid can not get into the pool water!

The liquid can not be used on chrome steel surfaces!

IN SANDFILTER:

1. Before use the **DINAX® FILTER CLEANER F** make sure that the effluent water doesn't get back in the pool water!

The liquid can not get in the pool water.

2. If possible, the necessary amount of filter cleaning liquid (see. dosage) pour directly on the filter media and leave on for at least 2 hours. Then continue from the 4. point.

3. If it is not possible to feed the cleaning liquid directly into the sand filter then add slowly to the skimmer during backwashing under an operating pump.

Guidelines: filter-cleaning liquid should go through the length of pipe between the pool and the skimmer. The water passes approx. 2 meters per second, so for example. on a 10 meter section of pipe the water passes under approx. 5 seconds.

Once the filter cleaning fluid got into the filtration system, shut off the pump and let it work for 2 hours.

4. Then, continue flushing (to the drain!) until the water is clear.
5. This should be followed by a 30-40 second prefiltration, then restore the system to normal filtration!

IN FILTER ELEMENTS:

1. Remove the filter element from the filter housing and spray it with the cleaning liquid.
2. Leave it on for 5-20 minutes.
3. Remove the formed foam with a powerful water jet.
4. Replace the cleaned filter cartridge in the filter housing.

DOSAGE:

In case of private pool:

- for a filter diameter between 450-500 mm use 200-300 ml **DINAX® FILTER CLEANER F**

In case of community filtering equipment:

- calculated for filter volume: use 1 liter **DINAX® FILTER CLEANER F** for 100 liter pool water

AVAILABLE SIZES:

- 1 kg bottle
- 20 kg canister (returnable)



dinax®