

## IPARI EGYOSZLOPOS LÁGYÍTÓ BERENDEZÉSEK

Típus	Teljesítmény (m <sup>3</sup> /h)		Gyantatöltet (dm <sup>3</sup> )	Kapacitás (m <sup>3</sup> *nk°/reg)	Regenerálósó igény (kg/reg)	Csatlakozási méretek			Helyigény (mm)			Tömeg (kg)
	névleges	maximum				d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	H	Sz	M	
<b>Dinamatic-50 A/P-E</b>	3.6	4.6	100	350	20	1 ½"	1 ½"	Ø63	1150	750	1925	270
<b>Dinamatic-60 A/P-E</b>	4.7	6.0	120	420	24	1 ½"	1 ½"	Ø63	1200	750	1940	330
<b>Dinamatic-70 A/P-E</b>	6.0	7.7	160	560	32	1 ½"	1 ½"	Ø63	1450	900	1940	450
<b>Dinamatic-80 A/P-E</b>	7.0	9.0	200	700	40	1 ½"	1 ½"	Ø90	1500	900	1940	520
<b>Dinamatic-90 A/P-E</b>	8.1	10.4	220	770	44	1 ½"	1 ½"	Ø90	1700	1000	1950	570
<b>Dinamatic-100 A/P-E</b>	10.1	13.0	300	1050	60	1 ½"	1 ½"	Ø110	2000	1250	2320	790
<b>Dinamatic-110 A/P-E</b>	15.8	20.3	500	1750	100	2"	2"	Ø110	2200	1400	2350	1280
<b>Dinamatic-120 A/P-E</b>	23.0	29.4	780	2730	156	DN80	DN80	Ø150	2700	1800	2350	1800
<b>Dinamatic-130 A/P-E</b>	31.0	40.0	900	3150	180	DN80	DN80	Ø200	2900	1800	2650	2300

A/P: automatikus programozható kivitel